



DIP CRYSTAL UNITS

49S Seam Sealing Crystal

- . Very compact and thin(10.5*4.0*3.5mm MAX)
- . Frequency range of 3M~64M with Found
- . Low cost ,Wide frequency range,Excellent aging

1	Nominal Frequency 标称频率	3~64MHz
2	Hold ing 封装形式	49S
3	Vibration Mde 振动模式	AT CUT, FUND/3RD AT 切, 基波/三倍波
4	Frequency Tolerance @ 25±3°C 调整频差	±10PPM / ±20PPM/ ±30PPM
5	Frequency Stability@ 6 工作温度条件下的频率容差	±10PPM / ±20PPM/ ±30PPM
6	Operating Temperature Range 工作温度	-20~+70°C / -40~85°C
7	Store Temperature Range 存储温度	-55~+125°C
8	Equivalency Resistance 等效电阻	20~200 Ω max
9	Load Capacitance 负载电容	10~32PF
10	Drive Level 激励功率	100 μ W max
11	Insulation Resistance 绝缘阻抗	>500MΩ at DC 100V±15V
12	Aging 老化	±3PPM/year max



HUBEI JINGMAO ELECTRONICS CO., LTD.

湖北晶茂电子科技有限公司

CRYSTAL CERAMIC DIP 49S DIMENSION

PACKAGE DIMENSIONS:Unit: mm

